WANG FUNG OFFICE SUPPLIES LTD.
TEL: 2461 6700 EMAIL: SALES@WANGFUNG.COM.HK



Model Overview

BONSAII SHREDDERS

bonsaii Sino-German Cooperation

	Bonsaii 4S16	Bonsaii 4S23	Bonsaii 4S30	Bonsaii 5S30	Bonsaii 3S16	Bonsaii 3S23	Bonsaii 3S30
Rate	220-240 / 50-60Hz	220-240 / 50-60Hz	220-240 / 50-60Hz	220-240 / 50-60Hz	220-240 / 50-60Hz	220-240 / 50-60Hz	220-240 / 50-60Hz
Motor	DC	DC	DC	DC	DC	DC	DC
Shred capacity	≤6/80gA4	≤8/80gA4	≤10/80gA4	≤5/80gA4	≤12/80gA4	≤14/80gA4	≤18/80gA4
Shred funtion	CD/Credit card/staples/clip	CD/Credit card/staples/clip	CD/Credit card/staples/clip	CD/Credit card/staples/clip	CD/Credit card/staples/clip	CD/Credit card/staples/clip	CD/Credit card/staples/clip
Shred type	Micro cut	Micro cut	Micro cut	Micro cut	Cross cut	Cross cut	Cross cut
Shred size (mm)	2*10	2*10	2*10	1*6	4*35	4*35	4*35
Security level	4	4	4	5	3	3	3
CD throat	Y	Y	Y	Y	Y	Y	Y
Shred speed per piece	2.2m/min	2.2m/min	2.2m/min	2.2m/min	2.2m/min	2.2m/min	2.2m/min
Shred speed	2.2m/min	2.0m/min	1.8m/min	2.2m/min	2.2m/min	2.0m/min	1.8m/min
Shred delayed(S)	2~5s	2~5s	2~5s	2~5s	2~5s	2~5s	2~5s
Shred capacity for CD	1	1	1	1	1	1	1
Solid cutter	Y	Y	Y	Y	Y	Y	Y
cooling fan system	yes	yes	yes	yes	yes	yes	yes
Continuous shred capacity	1 hour	2 hours	4 hours	4 hours	1 hour	2 hours	4 hours
Bin volume	16L	23L	30L	30L	16L	23L	30L
CD bin volume	1.4L	1.4L	1.4L	1.4L	1.4L	1.4L	1.4L
Noise	58dB	58dB	58dB	58dB	58dB	58dB	58dB
Product net weight (kg)	10.0kg（+/-0.5）	11.5kg（+/-0.5）	17.5kg（+/-0.5）	17.5kg（+/-0.5）	10.0kg（+/-0.5）	11.5kg（+/-0.5）	17.5kg（+/-0.5）
Rated power (W)	240W	250W	280W	280W	240W	250W	280W
Rated current (A)	1.2A	1.4A	1.5A	1.5A	1.2A	1.4A	1.5A
Overhearting protection	Y	Y	Y	Y	Y	Y	Y
Overloading protection	Y	Y	Y	Y	Y	Y	Y
Auto revese	Y	Y	Y	Y	Y	Y	Y
Auto start	Y	Y	Y	Y	Y	Y	Y
Auto stop	Y	Y	Y	Y	Y	Y	Y
Product size (mm)(L*W*H):	345x240x510	360x270x570	410x305x620	410x305x620	345x240x510	360x270x570	410x305x620
Warranty	1 Year on-site guarantee	1 Year on-site guarantee	1 Year on-site guarantee	1 Year on-site guarantee	1 Year on-site guarantee	1 Year on-site guarantee	1 Year on-site guarantee